

Colligo Marine Line Terminator Sizing Chart

	A	B	C	D	E	F	G						
Part Number	Pin Size with Sleeve	Hole Size without Sleeve	Overall Width	Pin Center Depth	Overall Diameter	Recommended line size	Slot Width	Lashing Line Slot Size	Lashing Holes	Safe Working Load (lbs-f)	Break Strength (lbs-f)	Weight	Comments
CSS70	0.25" (6.4mm)	0.25" (6.4mm)	.19" (6mm)	.97" (24.6mm)	.353" (9mm)	3-6 mm	.7" (18mm)	1/4" (6.4mm)	2	4,000	8,000	.8 oz (23grams)	No Sleeve, Use PTFE for Isolation
CSS71	.5" (12.8mm)	.625" (15.875mm)	.313"(7.94mm)	.743" (18.86mm)	.67" (17mm)	7-9 mm	.98" (25mm)	1/4" (6.4mm)	4	10,000	20,000	4.2 oz (120 grams)	
CSS72	.625" (15.875mm)	.875" (22.23)	.51" (13mm)	.625(15.89mm)	.87(22mm)	11-13 mm	1.26"(32mm)	1/4" (6.4mm)	4	15,000	30,000	6.1 oz (172 grams)	
CSS73	.625" (15.875mm)	.875" (22.23)	.787" 20mm)	1.26" (32mm)	1.89" (48mm)	15-17 mm	1.57" (40mm)	5/16" (8mm)	4	25,000	50,000	12.5 oz (355 grams)	
CSS74	0.875" (22.225mm)	1.25" (31.75mm)	.875" (22mm)	1.96" (49.78)	2.2" (56mm)	5-7 mm	2.4" (61mm)	5/16" (8mm)	3	4,000	8,000	2 oz (51 grams)	Lite Weight "Mini" Series
CSS75	.5" (12.8mm)	.625" (15.875mm)	.353" (9mm)	.564" (14.33)	1.18" (30mm)	7-9mm	.98" (25mm)	1/4" (6.4mm)	4	6,000	12,000	2.6 oz (71 grams)	Furler Terminator
CSS76	N/A	1" (25.4 mm)	1.18" (30 mm)	1.5" (38 mm)	4.72" (120 mm)	17-20mm	.827" (21 mm)	5/16" (8mm)	4	35,000	70,000	1 lb 12 oz (790 grams)	18 mm
CSS77	N/A	1.25" (31.76mm)	1.18" (30 mm)	1.97" (50 mm)	5.98" (152 mm)	20-25mm	1.02"(26 mm)	5/16" (8mm)	4	50,000	100,000	3 lbs 7.5 oz (1574 grams)	23-25 mm
CSS71-O	N/A	N/A	.313"(7.94mm)	N/A	.67" (17mm)	7-9 mm	.98" (25mm)	N/A	N/A	10,000	20,000	4.1 oz (117 grams)	Open line terminator 7-9 mm line
CSS72-O	N/A	N/A	.51" (13mm)	N/A	.87(22mm)	11-13 mm	1.26"(32mm)	N/A	N/A	15,000	30,000	6.1 oz (172 grams)	Open line terminator 11-13 mm line

